

# XTREME ACCESSORIES

UNDER CONCRETE SLAB VAPOR BARRIER
MASTER FORMAT #033000 - VAPOR BARRIER

#### XTREME SLM

### **DESCRIPTION**

Tex-Trude Xtreme Self Level Membrane (SLM) is a two component solvent free polymer-modified urethane asphalt. Xtreme SLM is designed to be installed around multiple penetrations (pipes) protruding through the vapor barrier and slab. When used correctly, Xtreme SLM will form a consistent membrane around pipes and penetrations working with the Xtreme Vapor Barrier to form a monolithic system to protect the building against moisture intrusion.



## **INSTALLATION**

Prior to installation, perform a visual inspection of the vapor barrier and the penetrations to insure all dust, dirt, debris, and moisture have been removed. It is important to apply the Xtreme SLM liberally, around all penetrations, and on top of the vapor barrier at a minimum of 90 mils. Overlap the Xtreme SLM on the vapor barrier six inches or more, to comply with the ASTM 1643. Be sure to pour a monolithic system were the Xtreme SLM has fully sealed around all penetrations and over laps the vapor barrier to secure proper coverage.

Warm conditions: Store out of direct sunlight. Perform normal installation, using industry knowledge of the guidelines for vapor barriers.

Cold conditions: In cold weather do not apply in temperatures below 40 degrees. Follow all instructions on the labels on the Xtreme SLM containers.





### **TECHNICAL DATA**

| Technical Data Xtreme SLM  |         | Packaging Xtreme SLM       |                    |
|----------------------------|---------|----------------------------|--------------------|
| Thickness                  | 90 mil  | Pail                       | 2 gallon pail unit |
| Permeance                  | 0.01    | Pails Per Pallet           | 36                 |
| Elongation                 | 125%    | Volume                     | 1.24 Unit          |
| Pot Life at 75 degrees     | 45 min  | Coverage per sq ft         | Approx. 16 sq ft   |
| Initial Cure at 75 degrees | 1 hour  | Color                      | Black              |
| Final Cure at 75 degrees   | 8 hours | Cold Weather<br>Resistance | Excellent          |

## LIMITED WARRANTY

Tex-Trude warrants this product to meet the published specifications and to be free of defects in workmanship and materials at the time of shipment from our factory. If any Xtreme material proves to contain manufacture defects that substantially affect the performance, then Tex-Trude will at their option replace the material or refund the purchase price. This limited warranty is the only warranty offered by Tex-Trude, LP as it relates to Xtreme products. There are no other warranties, including the implied warranties of merchantability or fitness for a particular purpose. Tex-Trude specifically disclaims liability for any incidental, consequential, or other damages.



